

ADK-DIP2M2.8-12L



## SPECIFICATION

Model NO.

ADK-DIP2M2.8-12L

**Camera**

Image Sensor	IMX322
Main processor	S2L
Resolution	1080P
Effective Pixels	1920(H)*1080(V)
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec
Sync System	External
Usable Illumination	0.01Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network

## **Lens**

Focus Length	2.8-12mm
Focus Control	Manual
Lens Type	Manual

Pixels	3M Pixels
<b>Night Vision</b>	
Infrared LED	☉ 5X21PCS
Infrared Distance	20M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4, HTTP, TCP/IP, FTP, NTP, RTSP, UDP, SMTP, DNS, DDNS
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Support
WIFI	N/A
Video Delay	0.3S (Within the Lan)
Main Stream	1920*1080@30fps

Sub Stream	704*576@30fps, 352*288@30fps
IE Brower	IE6-11, Google Chrome(IE Tab), Firefox(IE Tab)
Smart Phone	iPhone, iPad, Android, Android Pad

## Camera Features

Day/Night	Color/ B&W (IR-CUT )
Compression	H.264/JPEG,Support record AVI format.
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
WDR	YES
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi,

## General

Housing	Plastic
---------	---------

Lens Angle Adjustment	NO, Without Bracket
IR Cut Filter	YES
Operation Temperature	-10 ~ +50 RH95% Max
Storage Temperature	-20 ~ +60 RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	∅ 149 x 99(H)mm
Weight	750g

