


IP Video Intercom Device

WIDEO-DOMOFON IP



Model : adk video door phone3

- *support onvif for used in network video recorder or vms software
- *support sip for connect to ip pure pbx
- *support mobile software ios / android
- *support windows software
- *support 3 door
- *support poe and 12 v dc



| ADK Video Door Phone3 | |
|----------------------------|--|
| Image sensor | 1/3" SONY 960H CCD, DSP Effio-E, Day/Night |
| Sensitivity | 0.01 lux (Color) / 0.005 lux (B/W) / 0 lux (IR illumination) |
| Lens | 3.7 mm, F2.0 |
| Field of view | 65° (horizontal), 51° (vertical) |
| Field of view adjustment | +/- 45° |
| Minimum operating distance | 0.2 m |
| Zoom | Digital |
| Noise reduction | 2DNR |

| | |
|---------------------------------|--|
| Shutter time | 1/50 ~ 1/10000 s |
| Shutter mode | Auto |
| Ringer tone patterns | Set by the user |
| Other features | Progressive scan |
| Video | |
| Compression | H.264 BP/MP, Motion JPEG |
| Video streaming | Main, additional: H.264/MJPEG, H.264/H.264, MJPEG/MJPEG |
| Resolution | Main stream: 960x576, 720x576 (Full D1), 704x576 (D1), Additional stream: 704x576 (D1), 704x288 (2CIF), 352x288 (CIF), 176x144 (QCIF) |
| Framerate | Up to 25 fps in all resolutions |
| Bitrate | 32 kbps ~ 16 Mbps |
| Image settings | Brightness, contrast, saturation, hue, BLC, AGC, wight balance, exposure auto, ATR |
| Subtitles | Title, date, time, weekday, bitrate, framerate, number of connections |
| Audio | |
| Audio output | Built-in speaker |
| Audio input | Built-in microphone |
| Compression | G.711 (u-law) |
| Other features | Two-way audio |
| Illumination | |
| IR illumination | IR LED (3rd generation, 1 pcs) |
| Control | Auto, ON/OFF |
| Operating mode | By IR sensor, by video viewing, continuous |
| Wavelength | 850 nm |
| Lighting angle | 58° |
| IR distance | Up to 10 m |
| Network & interfaces | |
| Network interface | 10Base-T/100Base-TX |
| Network protocols | TCP/IP, IPv4/v6, SIP v.2.0, VPN, STUN, HTTP, HTTPS, FTP, SMTP, DNS, DDNS, DHCP, PPPoE, RTSP, UDP, NTP, ONVIF 2.41, Modbus TCP |
| Connection | DHCP, static IP address |
| Security | Multilevel user access control |
| Users | Password protection (up to 3 accounts) |
| SIP | |
| The number of SIP-accounts | 2 |
| SIP-call subs | Up to 5 |

| | |
|-------------------------------|---|
| DTMF modes | RFC2833, SIP INFO, in-band |
| Recording & events | |
| Events | Motion detection, network failure, call button pressing |
| Motion detection | Build-in video motion detector, up to 4 detection zones (sensitivity adjustment) |
| E-mail notification | At events: Images |
| FTP | At events: Images, video |
| Operation | |
| Power | DC12V, 0.6 A |
| Power consumption | 7.2 W |
| Electric current (max) | 1A (pins 1A, 1V) |
| Operating temperature | -40°C ~ +50°C |
| Ingress protection | IP54 |
| Housing material (housing) | Metal |
| Dimensions | 73x166x51 mm |
| Weight | 570 g |
| Color | Dim black / metallic grey |
| Control | Beward Intercom professional software (included) |
| System requirements | OS Windows 8/7/Vista, Internet Explorer 9.0 iOS 6.0-9 or higher / OS Android 4.0 or higher |
| Package contents | |
| Package contents | Panel (with the lens) |
| | Mount (it consists of 2 parts) |
| | Secret screw |
| | RJ-45 connectors (2 pcs) |
| | Junction box |
| | Fixing set |
| | Clip connector |
| | CD with manuals and software |
| | Package |

شرکت کاوش فن پرشیا نماینده رسمی ای دی کی در ایران

آدرس : میدان ولیعصر جنب پاساژ ایرانیان خیابان شقایق پلاک 8 واحد 1

فکس : 021 8889 3511

تلفن : 021 8894 1813