



WWW.ADK-SECURITY.COM

ADK SECURITY

9ch 3MP/4ch 5MP 2HDD

Model : ADK-2009

- P2P cloud service, including cloud connecting, cloud monitoring, cloud transmitting to access IPC and NVR at any time and any place
- Support Onvif protocol, support High profile S, High profile G, compatible with different IP camera that based on Onvif, RTSP standard
- Support megapixel HD network video preview, storage and playback;
- Support search, playback and backup by event;
- Support all channel image display on one screen at same time, support 4 channels' image display by mainstream, and 4 channels playback;
- Support monitor PTZ on preview mode
- Offer CMS for free

Model Number	Adk-2009	
Operating System	Embedded LINUX operating system	
Image Code Control	Image code quality adjustable, variable bitstream and constant bitstream optional	
Dual Stream	Each channel can set main stream and sub stream	
Video Standard	1080P(1920×1080)30fps/960P/(1280×960)/720P(1280×720)30fps	
Monitoring Image Quality	1080P(1920×1080) / 960P/(1280×960)/720P(1280×720)	
Image Motion Detection	Each screen can set multiple detection areas and set 6-level sensitivity	
Recording Playback Quality	Any 9ch 960ch playback, 4ch 5MP/3MP/1080P playback simultaneously.	
Region Cover	Every channel can set 4 cover regions (IPC Support)	
Recording Mode	Support manual , auto, dynamic detection, alarm trigger record mode(Partly needs IPC Support)	
Backup Way	Support U disk, USB mobile HDD, USB DVD-RW. network storage and backup	
Operation Way	Mouse, remote control, front panel	
Local Login	User name and password	
Recording Storage	Local HDD, network	
External Ports	Video Inputs	①9×(1920*1080)+sub[960*576]+4Ref.+4Play 9ch 2.0MP IP Camera
		②9×(1280*960)+sub[720*576]+4Ref.+9Play 9ch 1.3MP IP Camera
		③9×(2048*1536)+sub[960*576]+4Ref.+4Play 9ch 3.0MP IP Camera
		④4x(2592*1944)+sub[960*576]+4Ref.+4Play 4ch 5.0MP IP Camera

	Audio Input	16ch network audio input
	Video Output	1ch VGA+1ch HDMI
	Audio Output	1ch RCA output
	Network Port	1 RJ45,10M/100M/1000M self-adaptive LAN port
	USB Port	3 USB 2.0 ports (one on front panel, two on rear panel)
	Wireless Port	3G, WIFI
HDD	HDD Port	2 SATA HDD Port
	MAX Capacity	Each port supports MAX 4TB HDD
Mobile Surveillance		Support(iPhone, Windows Mobile, BlackBerry, Symbian, Android) smart phone
Power Supply		12V3A
Power Consumption		≤25W (without HDD)
Working Temperature		-10°C~ +55°C
Working Humidity		10%-90%
Dimension		Equipment : 350mm×240mm×70mm, Packing : 409mm×365mm×129mm
Weight(without HDD)		N.W. : 1.7Kg ; With packing : 2.89Kg
Outside Carton		5 pcs/carton. 675mm×425mm×385mm ; Weight : 15.22 Kg
Installation Way		Desktop Installation



WWW.ADK-SECURITY.COM