

# Hi3536 H.265 64CH 8MP NVR ان وی آر ۶۴ کانال فور کی MODEL: ADK-4264S-4K

## ADK

Front Panel:



Back Panel:



Software interface:



### Product highlights:

- Support H.265+/H.265/H.264 coding front end adaptive access.
- Support ONVIF, Highprofile S, Highprofile G, and can be connected to network cameras that comply with ONVIF, RTSP standards made by many major manufacturers.
- Support NVR local Intelligence: target count, object left/lost, area detection, line crossing.
- Support IPC front-end Intelligence: various intelligent detection access and linkages such as line crossing, wondering, face, license plate, audio input abnormality, virtual focus and scene change.
- Support AEeye P2P cloud services, through cloud access, cloud monitoring, cloud forwarding to achieve any terminal access to NVR anytime, anywhere.
- Support immediate playback function under preview screen without affecting other channel preview.
- Support for adaptive bit stream preview and playback 4 screen maximum support 1920\*1080, single screen 3840\*2160.
- Provide networked centralized monitoring and management software.

### NVR Technical Parameter:

|                       |                       |   |
|-----------------------|-----------------------|---|
| <b>Product Model</b>  |                       | <b>ADK-4264S-4K</b>   |
| Operating System      |                       | Embedded LINUX operating system   |
| Video Standard        |                       | H.265+/ H.265/H.264   |
| Intelligent Support   | NVR support           | Target count, object left/lost, area detection, line crossing   |
|                       | IPC support           | Various intelligent detection access and linkages such as line crossing, wondering, face, license plate, audio input abnormality, virtual focus and scene   |
| Video & Audio Input   | Video Input           | 64ch 4K and below resolution H.265+/H.265/H.264 IP camera   |
|                       | Bandwidth             | 216M  |
|                       | Audio Input           | IPC composite stream network audio input  |
| Video & Audio Output  | HDMI Output           | 1CH , Resolution : 4K(3840×2160)/30Hz , 1920×1080/60Hz , 1600×1200/60Hz , 1280×1024/60Hz , 1280×720/60Hz , 1024×768/60Hz  |
|                       | VGA Output            | 1CH , Resolution : 1920×1080/60Hz , 1280×1024/60Hz , 1280×720/60Hz , 1024×768/60Hz  |
|                       | Audio Output          | 1CH , RCA port ( Linear level , impedance : 1KΩ )   |
|                       | Preview Split         | 1/4//9/16/25/36/64 screen   |
| Video & Audio Coding  | Video Resolution      | 8MP/5MP/4MP/3MP/1080P and below resolution  |
|                       | Synchronized Playback | 16ch/9ch/4ch Synchronized Playback ( Different in various access modes )  |
|                       | Network Port          | 1 x RJ45 10M/100M/1000M adaptive Ethernet port  |
|                       | USB Port              | Front 1x USB2.0; Rear 1x USB2.0   |
| HDD                   | HDD Port              | 4x SATA   |
|                       | MAX Capacity          | Each port up to 8TB   |
| Network Management    | Network Protocol      | UPnP (Plug & Play), SNMP (Simple Network Management), NTP (Network Timekeeping), SADP (Device Network Search), SMTP (Mail Service), NFS (Access NAS), iSCSI (IP SAN Application), PPPoE (Dial-up Internet access), DHCP (automatically obtain IP address) |
| P2P Remote Monitoring | AEeye                 | Supports iPhone, iPad, Android Smart phone  |
|                       |                       | Supports Windows 7 and above computer client, supports Apple MAC computer client  |
| Power Supply          |                       | DC 12V6A (internal adapter)   |
| Working Temperature   |                       | -10°C-- + 55°C  |
| Working Humidity      |                       | 10%-90%   |
| Power Consumption     |                       | ≤30W (without HDD)  |
| Dimensions            |                       | Device : 440mm×356mm×68.5mm Packing :555mmX450mmX130mm  |
| Weight (Without HDD)  |                       | N.W. : 5.7Kg ; Packing : 6.9Kg  |
| Outside Carton        |                       | 4 pcs/carton. Dimension : 580mm×575mm×480mm ; Packing : 30Kg  |
| Installation Method   |                       | Desktop installation  |